


## Latest Promotions

Picture	Item No.	Unit Price (<100PCS)	Unit Price (≥ 100PCS)	Specification	Remarks
	KIR-2421CN20			Color 1/4" SHARP,420 TV Lines Low Illumination	<b>IR LED: ∅ 5X24PCS IR LED working distance:20M</b> Water resistance:IP66 Cable built-in bracket Lens: Board Lens 3.6mm/F2.0 Dimension:175(W) x124(H) x83(D)mm Weight:830g
	KIR-633CN20			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KIR-2365CN20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
 <b>HOT!</b>	KIR-2421CN25			Color 1/4" SHARP,420 TV Lines Low Illumination	<b>IR LED: ∅ 5X30PCS IR LED working distance:25M</b> Water resistance:IP66 Cable built-in bracket Lens: Board Lens 3.6mm/F2.0 Dimension:201(W) x82(H) x75(D)mm Weight:850g
	KIR-633CN25			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KIR-2365CN25			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
	KIR-673CN25			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	
 <b>HOT!!</b>	KIR-2421CK20			Color 1/4" SHARP,420 TV Lines Low Illumination	<b>IR LED: ∅ 5X24PCS IR LED working distance: 20M</b> Built-in bracket, 3-Axis direction bracket Lens: Board Lens 3.6mm/F2.0 Dimension:175(W) x124(H) x83(D)mm Weight:400g
	KIR-633CK20			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KIR-2365CK20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
 <b>HOT!!</b>	KIR-2421CK40			Color 1/4" SHARP,420 TV Lines Low Illumination	<b>IR LED: ∅ 5X42PCS IR LED working distance: 40M</b> Optional :700/650/600/420TV Lines Built-in 3-Axis bracket, External lens adjusting Lens: 4-9mm Manual Zoom Lens Dimension:228(W)x97(H)x82(D)mm Weight:1.4Kg
	KIR-633CK40			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KIR-2365CK40			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
	KIR-673CK40			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	
	KIR-2421CK60			Color 1/4" SHARP,420 TV Lines Low Illumination	<b>IR LED: ∅ 5X72PCS IR LED working distance: 60M</b> Built-in 3-Axis bracket, External lens adjusting Lens: 4-9mm Manual Zoom Lens Dimension:295(W)x120(H)x103(D)mm Weight:1.62Kg
	KIR-633CK60			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KIR-2365CK60			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
	KIR-673CK60			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	
 <b>HOT!!</b>	KIR-2421A40			Color 1/4" SHARP,420 TV Lines Low Illumination	<b>IR LED: ∅ 5X42PCS IR LED working distance: 40M</b> Optional :700/650/600/420TV Lines Built-in bracket, 3-Axis direction bracket Lens: 4-9mm Manual Zoom Lens New Housing Design, IP66 waterproof Dimension:200(W)x171(H)x83(D)mm Weight:1.4Kg
	KIR-633A40			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KIR-2365A40			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
	KIR-673A40			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	
	KIR-2421A60			Color 1/4" SHARP,420 TV Lines Low Illumination	<b>IR LED: ∅ 5X72PCS IR LED working distance: 60M</b> Built-in 3-Axis bracket, External lens adjusting Lens: 4-9mm Manual Zoom Lens Dimension:240(W)x186(H)x100(D)mm Weight:1.62Kg
	KIR-633A60			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KIR-2365A60			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
	KIR-673A60			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	

	KIR-2421K20			Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X24PCS IR LED working distance: 20M Built-in bracket, 3-Axis direction bracket Lens: Board Lens 3.6mm/F2.0 Dimension:86(W) x60(H) x55(D)mm Weight:400g
	KIR-633K20			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KIR-2365K20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
	KDV-2421SN20			Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof IR Dome Camera IR LED: $\varnothing$ 5X24PCS IR LED working distance: 20M Lens: Board Lens 3.6mm/F2.0 Dimension: $\varnothing$ 94 x 68.5(H)mm Weight:450g
	KDV-633SN20			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KDV-2365SN20			Color 1/3" Sharp, 600TV Lines Low Illumination,DWDR,OSD	
	KDV-673SN20			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	
	KDV-2421SH20			Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof IR Dome Camera IR LED: $\varnothing$ 5X24PCS IR LED working distance: 20M SONY/SHARP/NEXTCHIP Color CCD Optional :700/650/600/420TV Lines Lens: Board Lens 3.6mm/F2.0 Dimension: $\varnothing$ 94 x 69(H) mm Weight:400g
	KDV-633SH20			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KDV-2365SH20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
	KDV-673SH20			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	
	KDV-2421SHS30			Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof IR Dome Camera IR LED: $\varnothing$ 5X36PCS IR LED working distance: 30M SONY/Sharp/NEXTCHIP Color CCD Optional :700/650/600/420TV Lines 3-Axis bracket built-in Lens: 4-9mm Manual Zoom Lens Dimension: $\varnothing$ 131 x 93(H) mm Weight:800g
	KDV-633SHS30			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KDV-2365SHS30			Color 1/3" Sharp, 600TV Lines Low Illumination,DWDR,OSD	
	KDV-673SHS30			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	
	KDV-2421SHT30			Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof IR Dome Camera IR LED: $\varnothing$ 5X36PCS IR LED working distance: 30M SONY/Sharp/NEXTCHIP Color CCD Optional :700/650/600/420TV Lines 3-Axis bracket built-in Lens: 4-9mm Manual Zoom Lens Dimension: $\varnothing$ 131 x 93(H) mm Weight:800g
	KDV-633SHT30			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KDV-2365SHT30			Color 1/3" Sharp, 600TV Lines Low Illumination,DWDR,OSD	
	KDV-673SHT30			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	
	KDV-2421N45	\$26.8	\$26.8	Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof Dome Camera SONY/SHARP/NEXTCHIP CCD Optional :700/650/600/420TV Lines 3-Axis bracket built-in Lens: 4-9mm Manual Zoom Lens USD2 extra for 2.8-12mm Manual Zoom Lens Dimension: $\varnothing$ 142x 100(H) mm Weight: 1kg
	KDV-633N45	\$29.9	\$29.8	Color 1/3" SONY, 420 TV Lines Low Illumination	
	KDV-2365N45	\$36.8	\$36.8	Color 1/3" Sharp, 600TV Lines Low Illumination,DWDR,OSD	
	KDV-673N45	\$45.8	\$45.8	Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	

**Weatherproof IR Cameras (varifocal lens)** "Reliable Digital Security Products Manufacturer"

Picture	Item No.	Unit Price (<100PCS)	Unit Price ( $\geq$ 100PCS)	Specification	Remarks
	KIR-2421CNT30	\$33	\$31	Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing IR LED: $\varnothing$ 5X36PCS IR LED working distance:30M SONY/SHARP/NEXTCHIP CCD Optional :700/650/600/420TV Lines Water resistance:IP66 Cable built-in bracket Lens: 4-9mm Manual Zoom Lens USD2 extra for 2.8-12mm Manual Zoom Lens Dimension:228(W) x97(H) x82(D)mm Weight:880g
	KIR-633CNT30	\$36	\$34	Color 1/3" SONY, 420 TV Lines Low Illumination	
	KIR-338CNT30	\$39	\$37	Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
	KIR-2365CNT30	\$45	\$43	Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
	KIR-H639CNT30	\$50	\$48	Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
	KIR-R639CNT30	\$52	\$50	Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
	KIR-673CNT30	\$54	\$52	Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD,	



KIR-633CNT50		Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 8X36PCS IR LED working distance:50M
KIR-338CNT50		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Water resistance:IP66 Cable built-in bracket
KIR-2365CNT50		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Lens:4-9mm Manual Zoom Lens
KIR-H639CNT50		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens
KIR-R639CNT50		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Dimension:295(W) x120(H) x103(D)mm
KIR-673CNT50		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD,	Weight:1.5kg



KIR-2421CK40		Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing
KIR-633CK40		Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X42PCS IR LED working distance: 40M
KIR-338CK40		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/SHARP/NEXTCHIP CCD
KIR-2365CK40		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
KIR-H639CK40		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Built-in IP66 3-Axis bracket, External lens adjusting
KIR-R639CK40		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: 4-9mm Manual Zoom Lens
KIR-673CK40		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens
			Dimension:228(W)x97(H)x82(D)mm Weight:1.4Kg



KIR-2421CK60		Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing
KIR-633CK60		Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X72PCS IR LED working distance: 60M
KIR-338CK60		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/SHARP/NEXTCHIP CCD
KIR-2365CK60		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
KIR-H639CK60		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Built-in IP66 3-Axis bracket, External lens adjusting
KIR-R639CK60		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: 4-9mm Manual Zoom Lens
KIR-673CK60		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens
			Dimension:295(W)x120(H)x103(D)mm Weight:1.62Kg



KIR-2421A40		Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X42PCS IR LED working distance: 40M
KIR-633A40		Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD
KIR-338A40		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
KIR-2365A40		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in IP66 bracket, 3-Axis direction bracket
KIR-H639A40		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: 4-9mm Manual Zoom Lens
KIR-R639A40		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	USD2 extra for 2.8-12mm Manual Zoom Lens
KIR-673A40		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	New Housing Design, IP66 waterproof
			Dimension:200(W)x171(H)x83(D)mm Weight:1.4Kg



KIR-2421A60		Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X72PCS IR LED working distance: 60M
KIR-633A60		Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD
KIR-338A60		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
KIR-2365A60		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in IP66 bracket, 3-Axis direction bracket
KIR-H639A60		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: 4-9mm Manual Zoom Lens
KIR-R639A60		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	USD2 extra for 2.8-12mm Manual Zoom Lens
KIR-673A60		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD,	New Housing Design, IP66 waterproof
			Dimension:240(W)x186(H)x100(D)mm Weight:1.62Kg



ZOOM FOCUS

HOT!!

KIR-633NF40			Color 1/3" SONY, 420 TV Lines Low Illumination	Weatherproof Aluminium Housing
KIR-338NF40			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	IR LED: $\phi$ 5X42PCS IR LED working distance:40M
KIR-2365NF40			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	SONY/SHARP/NEXTCHIP CCD
KIR-H639NF40			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
KIR-R639NF40			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Water resistance:IP66 Cable built-in bracket IP66
KIR-673NF40			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR, OSD	Lens: 4-9mm Manual Zoom Lens
				USD2 extra for 2.8-12mm Manual Zoom Lens
				Dimension:Dimension:295(W)x105(H)x95(D)mm
				Weight:1.62Kg



KIR-633NK40			Color 1/3" SONY, 420 TV Lines Low Illumination	Weatherproof Aluminium Housing
KIR-338NK40			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	IR LED: $\phi$ 5X42PCS IR LED working distance:40M
KIR-2365NK40			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	SONY/SHARP/NEXTCHIP CCD
KIR-H639NK40			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
KIR-R639NK40			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Water resistance:IP66 Cable built-in bracket
KIR-673NK40			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR, OSD	Lens: 4-9mm Manual Zoom Lens
				USD2 extra for 2.8-12mm Manual Zoom Lens
				Dimension:260(W)x175(H)x105(D)mm
				Weight:1.62Kg



HOT!!

KIR-2421D40			Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\phi$ 5X42PCS IR LED working distance: 40M
KIR-633D40			Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD
KIR-338D40			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
KIR-2365D40			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket IP66
KIR-H639D40			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: 4-9mm Manual Zoom Lens
KIR-R639D40			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	USD2 extra for 2.8-12mm Manual Zoom Lens
KIR-673D40			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	New Housing Design, IP66 waterproof
				Dimension:220(W)x120(H)x83(D)mm Weight:1.4Kg



KIR-2421D60			Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\phi$ 5X72PCS IR LED working distance: 60M
KIR-633D60			Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD
KIR-338D60			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
KIR-2365D60			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket IP66
KIR-H639D60			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: 4-9mm Manual Zoom Lens
KIR-R639D60			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	USD2 extra for 2.8-12mm Manual Zoom Lens
KIR-673D60			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	New Housing Design, IP66 waterproof
				Dimension:272(W)x145(H)x104(D)mm Weight:1.62Kg



KIR-2421W30			Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\phi$ 5X36PCS IR LED working distance: 30M
KIR-633W30			Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD
KIR-338W30			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
KIR-2365W30			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket IP66
KIR-H639W30			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: 4-9mm Manual Zoom Lens
KIR-R639W30			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	USD2 extra for 2.8-12mm Manual Zoom Lens
KIR-673W30			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	IP66 waterproof
				Dimension:256(W)x143(H)x86(D)mm Weight:1.6Kg



KIR-2421W50			Color 1/4" SHARP,420 TV Lines Low Illumination	<b>IR LED: <math>\varnothing</math> 8X36PCS IR LED working distance: 50M</b> Optional :700/650/600/420TV Lines Built-in bracket, 3-Axis direction bracket <b>Lens: 4-9mm Manual Zoom Lens</b> USD2 extra for 2.8-12mm Manual Zoom Lens IP66 waterproof Dimension:259(W)x159(H)x104(D)mm Weight:1.92Kg
KIR-633W50			Color 1/3" SONY, 420 TV Lines Low Illumination	
KIR-338W50			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KIR-2365W50			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KIR-H639W50			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KIR-R639W50			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
KIR-673W50			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	



KIR-2421T30			Color 1/4" SHARP,420 TV Lines Low Illumination	<b>IR LED: <math>\varnothing</math> 5X36PCS IR LED working distance: 30M</b> Optional :700/650/600/420TV Lines Built-in bracket, 3-Axis direction bracket <b>Lens: 4-9mm Manual Zoom Lens</b> IP66 waterproof Dimension :200(W)x171(H)x83(D)mm Weight:1.4Kg
KIR-633T30			Color 1/3" SONY, 420 TV Lines Low Illumination	
KIR-338T30			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KIR-2365T30			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KIR-H639T30			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KIR-R639T30			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
KIR-673T30			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	



KIR-2421T50			Color 1/4" SHARP,420 TV Lines Low Illumination	<b>IR LED: <math>\varnothing</math> 8X36PCS IR LED working distance: 50M</b> Optional :700/650/600/420TV Lines Built-in bracket, 3-Axis direction bracket <b>Lens: 4-9mm Manual Zoom Lens</b> IP66 waterproof Dimension:240(W)x186(H)x100(D)mm Weight:1.62Kg
KIR-633T50			Color 1/3" SONY, 420 TV Lines Low Illumination	
KIR-338T50			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KIR-2365T50			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KIR-H639T50			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KIR-R639T50			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
KIR-673T50			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	




KIR-633ST50			Color 1/3" SONY, 420 TV Lines Low Illumination	<b>IR LED: <math>\varnothing</math> 8X36PCS IR LED working distance: 50M</b> <b>Built-in Auto temperature control</b> SONY/SHARP/NEXTCHIP CCD Optional :700/650/600/420TV Lines <b>Lens: 8-20mm Manual Zoom Lens</b> Dimension :230(W) x180(H) x115(D)mm Weight:2.1kg
KIR-338ST50			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KIR-2365ST50			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KIR-H639ST50			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KIR-R639ST50			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
KIR-673ST50			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	



KIR-633G40			Color 1/3" SONY, 420 TV Lines Low Illumination	<b>IR LED: <math>\varnothing</math> 8X36PCS IR LED working distance: 50M</b> <b>Lens: 8-20mm Manual Zoom Lens</b> Dimension :255(W)x152(H)x144(D)mm Weight:1.8Kg
KIR-H639G40			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KIR-673G40			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD,	

# Weatherproof IR Cameras (fixed lens)

"Reliable Digital Security Products Manufacturer"

Picture	Item No.	Unit Price (<100PCS)	Unit Price (≥ 100PCS)	Specification	Remarks
	KIR-1089CN20			Color 1/3" CMOS, 600 TV Lines	Weatherproof Aluminium housing
	KIR-2421CN20			Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\phi$ 5X24PCS IR LED working distance:20M
	KIR-633CN20			Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD
	KIR-338CN20			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :650/600/420TV Lines
	KIR-2365CN20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Water resistance:IP66 Cable built-in bracket
	KIR-H639CN20			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: Board Lens 3.6mm/F2.0
	KIR-R639CN20			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Dimension:175(W) x69(H) x55(D)mm Weight:830g
 <b>HOT!!</b>	KIR-2421CN25			Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing
	KIR-633CN25			Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\phi$ 5X30PCS IR LED working distance:25M
	KIR-338CN25			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/SHARP/NEXTCHIP CCD
	KIR-2365CN25			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
	KIR-H639CN25			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Water resistance:IP66 Cable built-in bracket
	KIR-R639CN25			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: Board Lens 3.6mm/F2.0
	KIR-673CN25			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD,	Dimension:200(W)x82(H)x75(D)mm Weight:850g
	KIR-2421CN30			Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing
	KIR-633CN30			Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\phi$ 5X36PCS IR LED working distance:30M
	KIR-338CN30			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/SHARP/NEXTCHIP CCD
	KIR-2365CN30			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
	KIR-H639CN30			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Water resistance:IP66 Cable built-in bracket
	KIR-R639CN30			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: CS Lens 6mm/F2.0
	KIR-673CN30			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD,	Dimension:228(W) x97(H) x82(D)mm Weight:880g
	KIR-2421CN50			Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing
	KIR-633CN50			Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\phi$ 8X36PCS IR LED working distance:50M
	KIR-338CN50			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/SHARP/NEXTCHIP CCD
	KIR-2365CN50			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
	KIR-H639CN50			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Water resistance:IP66 Cable built-in bracket
	KIR-R639CN50			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: CS Lens 6mm/F2.0
	KIR-673CN50			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD,	Dimension:295(W) x120(H) x103(D)mm Weight:1.3kg
 <b>HOT!!</b>	KIR-633NF30			Color 1/3" SONY, 420 TV Lines Low Illumination	Weatherproof Aluminium Housing
	KIR-338NF30			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	IR LED: $\phi$ 5X30PCS IR LED working distance:30M
	KIR-2365NF30			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	SONY/SHARP/NEXTCHIP CCD
	KIR-H639NF30			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
	KIR-R639NF30			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Water resistance:IP66 Cable built-in bracket
	KIR-673NF30			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR, OSD	Lens: Board Lens 3.6mm/F2.0 Dimension:200(W) x70(H) x65(D)mm Weight:930g



KIR-633NK30			Color 1/3" SONY, 420 TV Lines Low Illumination	Weatherproof Aluminium Housing
KIR-338NK30			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	IR LED: $\varnothing$ 5X30PCS IR LED working distance:30M
KIR-2365NK30			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Sharp/Sony/Nextchip CCD
KIR-H639NK30			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
KIR-R639NK30			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Water resistance:IP66 Cable built-in bracket
KIR-673NK30			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR, OSD	Lens: Board Lens 3.6mm/F2.0 Dimension:200(W) x78(H) x65(D)mm Weight:930g



HOT!!

KIR-1089CK20			Color 1/3" CMOS, 600 TV Lines with IR CUT	Weatherproof Aluminium Housing
KIR-2421CK20			Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X24PCS IR LED working distance: 20M
KIR-633CK20			Color 1/3" SONY, 420 TV Lines Low Illumination	Sharp/Sony/NEXTCHIP CCD
KIR-338CK20			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :650/600/420TV Lines
KIR-2365CK20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket IP66
KIR-H639CK20			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: Board Lens 3.6mm/F2.0
KIR-R639CK20			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Dimension:175(W) x124(H) x83(D)mm Weight:400g



KIR-2421N20			Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing
KIR-633N20			Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X24PCS IR LED working distance:20M
KIR-338N20			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/Sharp/Nextchip Color CCD
KIR-2365N20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Lens: Board Lens 3.6mm/F2.0
KIR-H639N20			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket IP66
KIR-R639N20			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Dimension :100(W) x77(H) x77(D)mm Weight:830g



KIR-2421N25			Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing
KIR-633N25			Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X30PCS IR LED working distance:20M
KIR-338N25			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :650/600/420TV Lines
KIR-2365N25			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket IP66
KIR-H639N25			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: Board Lens 3.6mm/F2.0
KIR-R639N25			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Dimension :162(W) x72(H) x69(D)mm Weight:830g
KIR-673N25			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	



KIR-2421Y25			Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X30PCS IR LED working distance:25M
KIR-633Y25			Color 1/3" SONY, 420 TV Lines Low Illumination	Sharp/Sony/Nextchip CCD
KIR-338Y25			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
KIR-2365Y25			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket
KIR-H639Y25			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: Board Lens 3.6mm/F2.0
KIR-R639Y25			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	New Housing Design, IP66 waterproof
KIR-673Y25			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension :162(W) x72(H) x69(D)mm Weight:620g



KIR-2421Y40		Color 1/4" SHARP,420TV Lines Low Illumination	IR LED: $\varnothing$ 5X48PCS IR LED working distance: 40M
KIR-633Y40		Color 1/3" SONY, 420 TV Lines Low Illumination	Sharp/Sony/Nextchip CCD
KIR-338Y40		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
KIR-2365Y40		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket
KIR-H639Y40		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: Board Lens 6mm/F2.0
KIR-R639Y40		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	New Housing Design, IP66 waterproof
KIR-673Y40		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension :215(W) x85(H) x78(D)mm Weight:800g



KIR-633N100		Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: 12pcs IR LED working distance: 100M
KIR-H639N100		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket IP66
KIR-673N100		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Lens: CS Lens 8mm/F2.0
			Dimension:275(W)x186(H)x123(D)mm Weight:2.4Kg



KIR-1089K20		Color 1/3" CMOS, 600 TV Lines	Weatherproof Aluminium Housing
KIR-2421K20		Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X24PCS IR LED working distance: 20M
KIR-633K20		Color 1/3" SONY, 420 TV Lines Low Illumination	Sharp/Sony/Nextchip CCD
KIR-338K20		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :650/600/420TV Lines
KIR-2365K20		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Lens: Board Lens 3.6mm/F2.0
KIR-H639K20		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket IP66
KIR-R639K20		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Dimension:86(W) x60(H) x55(D)mm Weight:400g



KIR-2421K30		Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing
KIR-633K30		Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X36PCS IR LED working distance: 30M
KIR-338K30		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/Sharp/Nextchip Color CCD
KIR-2365K30		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
KIR-H639K30		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket (IP66)
KIR-R639K30		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: Board Lens 6mm/F2.0
KIR-673K30		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension :153(W)x97(H)x82(D)mm Weight:700g



KIR-2421K40		Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing
KIR-633K40		Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X48PCS IR LED working distance: 40M
KIR-338K40		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/Sharp/Nextchip Color CCD
KIR-2365K40		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
KIR-H639K40		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket (IP66)
KIR-R639K40		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: Board Lens 6mm/F2.0
KIR-673K40		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension :153(W)x97(H)x82(D)mm Weight:700g



**HOT!!**

KIR-2421KB40			Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof Aluminium Housing
KIR-633KB40			Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X48PCS IR LED working distance: 40M
KIR-338KB40			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Sharp/Sony/Nextchip CCD
KIR-2365KB40			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
KIR-H639KB40			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Built-in 3-Axis bracket, External lens adjusting IP66
KIR-R639KB40			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: Board Lens 6mm/F2.0
KIR-673KB40			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension :200(W)x78(H)x81.5(D)mm Weight:800g



KIR-633K100			Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 10X12PCS IR LED working distance:100M
KIR-H639K100			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: CS Lens 12mm/F2.0
KIR-673K100			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension:273(W)x103(H)x119(D)mm Weight:2.51kg



KIR-2421S50			Color 1/4" SHARP,420 TV Lines Low Illumination	IR LED: $\varnothing$ 8X36PCS IR LED working distance: 50M
KIR-633S50			Color 1/3" SONY, 420 TV Lines Low Illumination	Sharp/Sony/Nextchip CCD
KIR-338S50			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
KIR-2365S50			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket
KIR-H639S50			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: CS Lens 8mm/F2.0
KIR-R639S50			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	IP66 waterproof
KIR-673S50			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension :175(W)x174(H)x95(D)mm Weight:1.3Kg



KIR-2421S40			Color 1/4" SHARP,420TV Lines	IR LED: $\varnothing$ 5X48PCS IR LED working distance: 40M
KIR-633S40			Color 1/3" SONY, 420 TV Lines Low Illumination	Sharp/Sony/Nextchip CCD
KIR-338S40			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
KIR-2365S40			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Built-in bracket, 3-Axis direction bracket
KIR-H639S40			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: Board Lens 6mm/F2.0
KIR-R639S40			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	IP66 waterproof
KIR-673S40			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension :175(W) x124(H) x83(D)mm Weight:800g

**Dome Cameras (fixed lens)** *"Reliable Digital Security Products Manufacturer"*



Picture	Item No.	Specification	Remarks
	KDP-1089S25	Color 1/3" CMOS, 600 TV Lines	Plastic Dome Camera
	KDP-2421S25	Color 1/4" SHARP,420TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD or CMOS
	KDP-633S25	Color 1/3" SONY, 420 TV Lines Low Illumination	
	KDP-338S25	Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
	KDP-2365S25	Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Lens: 3.6mm Board lens/F2.0
	KDP-H639S25	Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
	KDP-R639S25	Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Dimension : $\varnothing$ 87.5 x 58(H) mm
	KDP-673S25	Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Weight:300g



HOT!!

KDP-1089SA25			Color 1/3" CMOS, 600 TV Lines	Plastic Dome Camera SONY/SHARP/NEXTCHIP CCD or CMOS Optional :700/650/600/420TV Lines Lens: 3.6mm Board lens/F2.0 Dimension : $\varnothing$ 85x 54(H) mm Weight:200g
KDP-2421SA25			Color 1/4" SHARP,420TV Lines Low Illumination	
KDP-633SA25			Color 1/3" SONY, 420 TV Lines Low Illumination	
KDP-338SA25			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KDP-2365SA25			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KDP-H639SA25			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KDP-R639SA25			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
KDP-673SA25			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	



KDP-1089M45			Color 1/3" CMOS, 600 TV Lines	Plastic Dome Camera SONY/SHARP/NEXTCHIP CCD or CMOS Optional :700/650/600/420TV Lines Lens: 3.6mm Board lens/F2.0 Dimension : $\varnothing$ 118 x 74(H) mm Weight:350g
KDP-2421M45			Color 1/4" SHARP,420TV Lines Low Illumination	
KDP-633M45			Color 1/3" SONY, 420 TV Lines Low Illumination	
KDP-338M45			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KDP-2365M45			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KDP-H639M45			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KDP-R639M45			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
KDP-673M45			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	



HOT!!

KDV-1089SM20			Color 1/3" CMOS, 600 TV Lines with IR CUT	Vandalproof Dome Camera IR LED: $\varnothing$ 5X24PCS IR LED working distance: 20M SONY/Sharp/NEXTCHIP Color CCD or CMOS Optional :700/650/600/420TV Lines 3-Axis bracket built-in Lens: Board Lens 3.6mm/F2.0 Dimension: $\varnothing$ 94 x 69(H) mm Weight:550g
KDV-2421SM20			Color 1/4" SHARP,420 TV Lines Low Illumination	
KDV-633SM20			Color 1/3" SONY, 420 TV Lines Low Illumination	
KDV-338SM20			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KDV-2365SM20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KDV-H639SM20			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KDV-R639SM20			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
KDV-673SM20			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	



HOT!!

KDV-1089SN20			Color 1/3" CMOS, 600 TV Lines with IR CUT	Vandalproof Dome Camera IR LED: $\varnothing$ 5X24PCS IR LED working distance: 20M SONY/Sharp/NEXTCHIP Color CCD or CMOS Optional :700/650/600/420TV Lines 3-Axis bracket built-in Lens: Board Lens 3.6mm/F2.0 Dimension: $\varnothing$ 94 x 69(H) mm Weight:450g
KDV-2421SN20			Color 1/4" SHARP,420 TV Lines Low Illumination	
KDV-633SN20			Color 1/3" SONY, 420 TV Lines Low Illumination	
KDV-338SN20			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KDV-2365SN20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KDV-H639SN20			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KDV-R639SN20			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
KDV-673SN20			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	



KDP-1089SH20			Color 1/3" CMOS, 600 TV Lines	Plastic IR Dome Camera IR LED: $\varnothing$ 5X24PCS IR LED working distance: 20M SONY/Sharp/NEXTCHIP Color CCD or CMOS Optional :650/600/420TV Lines 3-Axis bracket built-in Lens: Board Lens 3.6mm/F2.0 Dimension: $\varnothing$ 94 x 69(H) mm Weight:300g
KDP-2421SH20			Color 1/4" SHARP,420 TV Lines Low Illumination	
KDP-633SH20			Color 1/3" SONY, 420 TV Lines Low Illumination	
KDP-338SH20			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KDP-2365SH20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KDP-H639SH20			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KDP-R639SH20			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	



HOT!!

KDP-1089SH25			Color 1/3" CMOS, 600 TV Lines	Plastic IR Dome Camera, white/black housing IR LED: $\varnothing$ 5X30PCS IR LED working distance: 25M 3-Axis bracket built-in, 360° adjustable direction, Easy Installation SONY/Sharp Color CCD or CMOS Optional :650/600/420TV Lines Lens: Board Lens 3.6mm/F2.0 Dimension: $\varnothing$ 100 x 70(H) mm Weight:300g
KDP-2421SH25			Color 1/4" SHARP,420 TV Lines Low Illumination	
KDP-633SH25			Color 1/3" SONY, 420 TV Lines Low Illumination	
KDP-338SH25			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KDP-2365SH25			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KDP-H639SH25			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KDP-R639SH25			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	



KDV-1089SH20			Color 1/3" CMOS, 600 TV Lines	Vandalproof IR Dome Camera IR LED: $\varnothing$ 5X24PCS IR LED working distance: 20M SONY/Sharp/NEXTCHIP Color CCD or CMOS Optional :700/650/600/420TV Lines 3-Axis bracket built-in Lens: Board Lens 3.6mm/F2.0 Dimension: $\varnothing$ 94 x 69(H) mm Weight:400g
KDV-2421SH20			Color 1/4" SHARP,420 TV Lines Low Illumination	
KDV-633SH20			Color 1/3" SONY, 420 TV Lines Low Illumination	
KDV-338SH20			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KDV-2365SH20			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KDV-H639SH20			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KDV-R639SH20			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
KDV-673SH20			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	



KDV-1089N25			Color 1/4" CMOS,600 TV Lines	Vandalproof Dome Camera SONY/SHARP/NEXTCHIP CCD or CMOS Optional :700/650/600/420TV Lines 3-Axis bracket built-in Lens: 3.6mm Board lens/F2.0 Dimension: $\varnothing$ 94x 85(H) mm Weight: 490g
KDV-2421N25			Color 1/4" SHARP,420 TV Lines Low Illumination	
KDV-633N25			Color 1/3" SONY, 420 TV Lines Low Illumination	
KDV-338N25			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KDV-2365N25			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KDV-H639N25			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KDV-R639N25			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	
KDV-673N25			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	





KDV-1089E25			Color 1/4" CMOS, 600TV Lines	2.5" Vandalproof Dome Camera SONY/SHARP/NEXTCHIP CCD or CMOS Optional :700/650/600/420TV Lines Lens: 3.6mm Board lens/F2.0 Dimension : $\varnothing$ 94 x 69(H) mm Weight:350g
KDV-2421E25			Color 1/4" SHARP,420 TV Lines Low Illumination	
KDV-633E25			Color 1/3" SONY, 420 TV Lines Low Illumination	
KDV-338E25			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	
KDV-2365E25			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	
KDV-H639E25			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
KDV-R639E25			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	


# Dome Cameras (varifocal lens)


"Reliable Digital Security Products Manufacturer"


Picture	Item No.	Unit Price (<100PCS)	Unit Price (≥ 100PCS)	Specification	Remarks
	KDP-1089BT45			Color 1/3" CMOS, 600 TV Lines	4.5" Plastic Dome Camera
	KDP-2421BT45			Color 1/4" SHARP, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD or CMOS
	KDP-633BT45			Color 1/3" SONY, 420 TV Lines Low Illumination	
	KDP-338BT45			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
	KDP-2365BT45			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	3-Axis bracket built-in
	KDP-H639BT45			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
	KDP-R639BT45			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens:4-9mm Manual Zoom Lens
	KDP-673BT45			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension:φ 118 x 106(H) mm Weight:520g
	KDP-2421RT45			Color 1/4" SHARP,420 TV Lines Low Illumination	4.5" Plastic Dome Camera
	KDP-633RT45			Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD
	KDP-338RT45			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
	KDP-2365RT45			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	IR LED: φ 5X21PCS IR LED working distance: 20M
	KDP-H639RT45			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
	KDP-R639RT45			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens:4-9mm Manual Zoom Lens
	KDP-673RT45			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens
					Dimension:φ 149 x 99(H) mm Weight:520g
	KDV-2421N35			Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof Dome Camera
	KDV-633N35			Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD or CMOS
	KDV-338N35			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
	KDV-2365N35			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	3-Axis bracket built-in
	KDV-H639N35			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
	KDV-R639N35			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: 4-9mm Manual Zoom Lens
	KDV-673N35			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens
					Dimension: φ 117x 92(H) mm Weight: 800g
	KDV-2421N45			Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof Dome Camera
	KDV-633N45			Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD or CMOS
	KDV-338N45			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
	KDV-2365N45			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	3-Axis bracket built-in
	KDV-H639N45			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
	KDV-R639N45			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: 4-9mm Manual Zoom Lens
	KDV-673N45			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens
					Dimension: φ 142x 100(H) mm Weight: 1kg
	KDV-2421DT45			Color 1/4" SHARP,420 TV Lines Low Illumination	2.5" Vandalproof Dome Camera
	KDV-633DT45			Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD
	KDV-338DT45			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
	KDV-2365DT45			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	3-Axis bracket built-in
	KDV-H639DT45			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	
	KDV-R639DT45			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: 4-9mm manual zoom Lens
	KDV-673DT45			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens
					Dimension : φ 140x 94(H) mm Weight:700g


	KDV-2421K35		Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof Dome Camera
	KDV-633K35		Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD
	KDV-338K35		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
	KDV-2365K35		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	3-Axis bracket built-in
	KDV-H639K35		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: 4-9mm Manual Zoom Lens
	KDV-R639K35		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	USD2 extra for 2.8-12mm Manual Zoom Lens
	KDV-673K35		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension: $\varnothing$ 118x 99(H) mm Weight: 600g


	KDV-2421K55		Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof Dome Camera
	KDV-633K55		Color 1/3" SONY, 420 TV Lines Low Illumination	SONY/SHARP/NEXTCHIP CCD
	KDV-338K55		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional :700/650/600/420TV Lines
	KDV-2365K55		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	3-Axis bracket built-in
	KDV-H639K55		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Lens: 4-9mm Manual Zoom Lens
	KDV-R639K55		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	USD2 extra for 2.8-12mm Manual Zoom Lens
	KDV-673K55		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	With dual voltage DC12V/AC24V add USD4.00 Dimension: $\varnothing$ 140x 120(H) mm Weight: 1.2kg


	KDV-2421KR45		Color 1/4" SHARP,420 TV Lines Low Illumination	4.5" Vandalproof Dome Camera
	KDV-633KR45		Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X21PCS IR LED working distance: 20M
	KDV-338KR45		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/Sharp/NEXTCHIP Color CCD
	KDV-2365KR45		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
	KDV-H639KR45		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	3-Axis bracket built-in
	KDV-R639KR45		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens:4-9mm Manual Zoom Lens
	KDV-673KR45		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens Dimension : $\varnothing$ 149x 99(H) mm Weight:1kg

 <b>HOT!!</b>	KDV-2421SHS30		Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof IR Dome Camera
	KDV-633SHS30		Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X36PCS IR LED working distance: 30M
	KDV-338SHS30		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/Sharp/NEXTCHIP Color CCD
	KDV-2365SHS30		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
	KDV-H639SHS30		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	3-Axis bracket built-in
	KDV-R639SHS30		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: 4-9mm Manual Zoom Lens
	KDV-673SHS30		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens Dimension: $\varnothing$ 131 x 93(H) mm Weight:800g


 <b>HOT!!</b>	KDV-2421SHT30		Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof IR Dome Camera
	KDV-633SHT30		Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X36PCS IR LED working distance: 30M
	KDV-338SHT30		Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/Sharp/NEXTCHIP Color CCD
	KDV-2365SHT30		Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
	KDV-H639SHT30		Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	3-Axis bracket built-in
	KDV-R639SHT30		Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: 4-9mm Manual Zoom Lens
	KDV-673SHT30		Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens Dimension: $\varnothing$ 131 x 93(H) mm Weight:800g


	KDV-2421CT30			Color 1/4" SHARP,420 TV Lines Low Illumination	Vandalproof IR Dome Camera
	KDV-633CT30			Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X36PCS IR LED working distance: 30M
	KDV-338CT30			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	SONY/Sharp/NEXTCHIP Color CCD
	KDV-2365CT30			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional :700/650/600/420TV Lines
	KDV-H639CT30			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	3-Axis bracket built-in
	KDV-R639CT30			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Lens: 4-9mm Manual Zoom Lens
	KDV-673CT30			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens Dimension: $\varnothing$ 275x 93(H) mm Weight:2.1kg

	KDV-2421W25			Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof &Vandalproof IR Dome Camera
	KDV-633W25			Color 1/3" SONY, 420 TV Lines Low Illumination	3-Axis bracket built-in
	KDV-338W25			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	IR LED: $\varnothing$ 5X30PCS IR LED working distance: 25M
	KDV-2365W25			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Optional:700/650/600/420TV Lines
	KDV-H639W25			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	4-9mm Manual Zoom Lens
	KDV-R639W25			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	USD2 extra for 2.8-12mm Manual Zoom Lens
	KDV-673W25			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Bracket included (IP66 waterproof) Dimension: $\varnothing$ 135x 110(H) mm Weight:2kg

	KDV-2421V25			Color 1/4" SHARP,420 TV Lines Low Illumination	Weatherproof &Vandalproof IR Dome Came
	KDV-633V25			Color 1/3" SONY, 420 TV Lines Low Illumination	IR LED: $\varnothing$ 5X30PCS IR LED working distance: 25M
	KDV-338V25			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	Optional:700/650/600/420TV Lines
	KDV-2365V25			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	4-9mm Manual Zoom Lens
	KDV-H639V25			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	USD2 extra for 2.8-12mm Manual Zoom Lens
	KDV-R639V25			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Bracket included (IP66 waterproof)
	KDV-673V25			Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Dimension: $\varnothing$ 140x 110(H) mm Weight:2kg


**Mini Speed dome Camera** *"Reliable Digital Security Products Manufacturer"*

Picture	Item No.	Specification	Remarks
	KPD-633D1	Color 1/3" SONY, 420TV Lines, Low Illumination	Vandalproof Mini PT Speed Dome camera Pan range: 0°~360° Continue (Not 355° )
	KPD-H639D1	Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Tilt range: 0°~90° Flip Pan Speed: Max 50°/sec Preset: 16
	KPD-R639D1	Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Weatherproof Outdoor IP66 RS485, Pelco D/P supported
	KPD-673D1	Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Lens: 4-9mm Manual Zoom Lens Size: $\varnothing$ 121x177mm; Weight: 2.8Kg

	KPD-633P1	Color 1/3" SONY, 420TV Lines, Low Illumination	Vandalproof Mini PT Speed Dome camera Pan range: 0°~360° Continue (Not 355° )
	KPD-H639P1	Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Tilt range: 0°~90° Flip Pan Speed: Max 50°/sec Preset: 16
	KPD-R639P1	Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Weatherproof Outdoor IP66 RS485, Pelco D/P supported
	KPD-673P1	Color 1/3" SONY Effio-E (NR, PM, MD), 700TV Lines Low Illumination, ATR,OSD	Lens: 4-9mm Manual Zoom Lens Size: $\varnothing$ 138x212mm; Weight: 2.8Kg


# 10X Mini Speed dome Camera

"Reliable Digital Security Products Manufacturer"

 <b>HOT!!</b>	KPD-CKAD1		10X, 1/4" Super HAD Sony Color CCD, 10X(f=3.8~38mm), Color 480TVL	Vandalproof Mini PTZ Speed Dome camera Pan range: 0°~360° Continue (Not 355°) Tilt range: 0°~90° Flip Pan Speed: Max 50°/sec Preset: 16
	KPD-SAMD1		SAMSUNG 10X SDM-100, 1/4" Super HAD Color CCD, ICR, 10X(f=3.8~38mm), Color 500TVL, Black 570TVL	<b>Weatherproof Outdoor IP66</b> RS485, Pelco D/P supported <b>10X optical zoom lens(f=3.8~38mm)</b> Size: Ø121x177mm Weight: 2.8Kg
 <b>HOT!!</b>	KPD-CKAP1		10X, 1/4" Super HAD Sony Color CCD, 10X(f=3.8~38mm), Color 480TVL	Vandalproof Mini PTZ Speed Dome camera Pan range: 0°~360° Continue (Not 355°) Tilt range: 0°~90° Flip Pan Speed: Max 50°/sec Preset: 16
	KPD-SAMP1		SAMSUNG 10X SDM-100, 1/4" Super HAD Color CCD, ICR, 10X(f=3.8~38mm), Color 500TVL, Black 570TVL	<b>Weatherproof Outdoor IP66</b> RS485, Pelco D/P supported <b>10X optical zoom lens(f=3.8~38mm)</b> Size: Ø138x212mm Weight: 2.8Kg



# Box Camera

"Reliable Digital Security Solution Manufacturer"

Picture	Item No.	≥	Specification	Remarks
	KCB-633B1		Color 1/3" SONY, 420 TV Lines Low Illumination	Standard Box Camera Iris control:DC/VIDEO
	KCB-639B1		Color 1/3" SONY, 540TV Lines Low Illumination	Dimension:110(W)x45(H)x55(D)mm Weight:380g


# Bullet camera

"Reliable Digital Security Products Manufacturer"

Picture	Item No.	≥	Specification	Remarks
	KBL-633B2		Color 1/3" SONY, 420 TV Lines Low Illumination	Lens:3.6mm Board Lens Dimension:ø 20 x 62(H) mm Weight:200g
	KBL-633PB		Color 1/3" SONY, 420 TV Lines Low Illumination	Lens:3.7mm Taper Pinhole Lens Dimension:ø 20 x 62(H) mm Weight:200g

# Hidden camera



"Reliable Digital Security Products Manufacturer"

Picture	Item No.	Unit Price (<100PCS)	≥	Specification	Remarks
	KHD-2421SD1			Color 1/4" SHARP,420 TV Lines Low Illumination	Smoke Detector Camera
	KHD-633SD1			Color 1/3" SONY, 420TV Lines, Low Illumination	Sharp/Sony/NEXTCHIP Color CCD
	KHD-338SD1			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	High resolution: 650/600/420TV Lines optional
	KHD-2365SD1			<b>Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD</b>	Lens:3.6mm Board Lens
	KHD-H639SD1			<b>Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD</b>	Dimension : ø 119 x 56(H) mm
	KHD-R639SD1			<b>Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up</b>	Weight:340g



KHD-2421SP2			Color 1/4" SHARP,420 TV Lines Low Illumination	PIR Spy Camera
KHD-633SP2			Color 1/3" SONY, 420TV Lines, Low Illumination	Sharp/Sony/Nextchip Color CCD
KHD-338SP2			Color 1/3" nextchip, 600TV Lines, DWDR, OSD	High resolution: 650/600/420TV Lines optional
KHD-2365SP2			Color 1/3" SHARP, 600TV Lines Low Illumination,DWDR,OSD	Lens: 3.7mm Taper Pinhole Lens
KHD-H639SP2			Color 1/3" SONY, 600TV Lines Low Illumination,DWDR,OSD	Dimension :70(W) x40(H) x119(D)mm
KHD-R639SP2			Color 1/3" SONY, 650TVLines Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Weight:340g

**IR LED** *"Reliable Digital Security Products Manufacturer"*

Picture	Item No.	Unit Price (<100PCS)	Specification	Remarks
	KLED-B80		Weatherproof of IR Illuminator	114pcs ø8-14µ IR IED Available IR distance:80m Size:150(L)*120(H)*88(W) Power: 12V DC MAX 16W Weight:1.91kg
	KLED-B130		Weatherproof of IR Illuminator	198pcs ø8-14µ IR IED Available IR distance:130m Size:200(L)*143(H)*88(W) Power: 12V DC MAX 28W Weight:2.8kg



Livraison gratuite à casablanca et les régions  
Livraison Par S2M pour toute commande hors casablanca



**0522 24 97 92**

\*\* Les Bons de commandes ==> par fax au 0522 24 97 92 ou bien par e-mail: [logiskay@gmail.com](mailto:logiskay@gmail.com)